

SYS20 Setup



**Rev A
11/12/2008**

CARVIN
carvinservice.com

SYS20

- (2) DCM2500
- (2) LSX2153
- (2) PRO50S Cables

AC cable



Plug in the AC cord, push firmly



DCM2500

Note: The DCM2500 has a soft start, meaning it takes 3 seconds to fully engage the sound.

Amp connection 1



DCM2500 1/4 CH 1



(1) LSX2153

Amp connection 2



DCM2500 1/4 CH 2




(2) LSX2153

Mixer connection

Connect your mixer to input 1 or 2 in the DCM2500, XLR or 1/4 inch Inputs.
For Carvin C-mixer setup look for SYS20-24U.

CAUTION – Always be certain that you are using genuine ¼ speaker cables when connecting your amplifier to a speaker; using standard shielded guitar cables or “patch cords” will cause damage to your equipment (note - Carvin genuine speaker cables will typically have grey shrink wrap on the plug ends)

Installation tips



Note: All of the buttons on the back of the DCM2500 should be out, including the bridge button. The yellow arrow in the picture indicates where the button is, note that it's recessed into the chassis, insert a pen into the hole and check to make sure it's in the out position.



Note: Full range will be engaged when you get the cabinet. If you decide to run the cabinet in Bi-Amp mode only the Twist-lock jacks will work not the ¼ inch jacks.